

The MFTSTH1-B is a battery powered Temperature and Humidity sensor that uses the latest Bluetooth technology BLE 5.0 sensor. The MFTSTH1-B accurately collects temperature and humidity in some of the most harshest environment, which makes monitoring any easy at any location. The MFTSTH1-B is a solution that resolves losses caused by unexpected temperature and humidity changes.

MFTSTH1-B SUPPORTS

Internal Temperature Sensor Internal Light Sensor BLE 5.0 FOTA LED Indicator

DEVICE BEHAVIOR

Reporting Frequency: Every 60 minutes Every 10 seconds Installation Time: <5 Minutes

SPECIFICATIONS

Waterproof: IP65

Dimensions: 0.23in x 0.17in x 0.06in Weight: 1.23oz (includes battery)

Battery: Replaceable CR2477 battery (1000mAh)

Battery Life: Standby Time

60 minute reporting: 3000 Days (8 years) 1 minute reporting: 2000 Days (6 years) 10 second reporting: 1850 Days (5 years)

Temperature accuracy (0-60°): \pm 0.2° (Typical long-term drift <0.02° C / year) Humidity accuracy (10% -90%): \pm 2% RH (long-term drift rate <0.25% RH / Y)

Transmission Range: up to 300m (Open Field)

Operating Temperature: $-30^{\circ} \sim +60^{\circ} (-22^{\circ} \text{ F} \sim 140^{\circ} \text{ F})$

Mounting: 3M Tape/Screw

ACCESSORIES

Included: 3M Tape Screws CR2477 Battery ALERTS

BLE 5.0

IP65 RATING

EASY INSTALLATION

WIDE TRANSMISSION RANGE

INTERNAL BATTERY

(up to 8yrs reporting every 60mins,

5yrs reporting every 10s, Replaceable)

NEAR REAL-TIME MONITORING

WIDE RANGE OF OPERATING TEMPS

FOR MORE INFORMATION CONTACT:

Phone: (866) MIFLEET Email: sales@mifleet.us www.MiFleet.us